PATENT - BRTC

In the Claims

Please amend Claims 1 and 56-62 as follows:

- 1. (Once Amended) A cleaning composition comprising:
 - a) a surfactant system,
 - an oxidoreductase with an α/β-hydrolase fold and a catalytic triad consisting of the amino acid residues serine, histidine and aspartic acid,

AMENDMENTS

- c) a hydrogen peroxide source, and
- d) an organic acid

wherein said composition comprises a pH of from 7.5 to 12.7.

- 56. (Once Amended) A fabric softening composition comprising
 - a) a surfactant system comprising a cationic surfactant comprising two long chain lengths,
 - an oxidoreductase with an α/β-hydrolase fold and a catalytic triad consisting of the amino acid residues serine, histidine and aspartic acid,
 - c) a hydrogen peroxide source and
 - d) an organic acid

wherein said composition comprises a pH of from 7.5 to 12.7.

- 57. (Once Amended) A method of cleaning comprising the step of contacting a fabric with a cleaning composition comprising a surfactant system, an oxidoreductase with an α/β-hydrolase fold and a catalytic triad consisting of the amino acid residues serine, histidine and aspartic acid, a hydrogen peroxide source and an organic acid, for fabric cleaning and/or fabric stain removal and/or fabric whiteness maintenance and/or fabric softening and/or fabric clour appearance and/or fabric dye transfer inhibition wherein said composition comprises a pH of from 7.5 to 12.7.
- 58. (Twice Amended) A method of cleaning comprising the step of contacting a hard surface with a cleaning composition comprising a surfactant system, an oxidoreductase with an a/B-hydrolase fold and a catalytic triad consisting of the amino acid residues serine, histidine and aspartic acid, a hydrogen peroxide source and an organic acid wherein said composition comprises a pH of from 7.5 to 12. 7.
- 59. (Once Amended) A method of cleaning comprising the step of contacting a dishware with a cleaning composition comprising a surfactant system, an oxidoreductase with an α/β-hydrolase fold and a catalytic triad consisting of the amino acid residues serine, histidine and aspartic acid, a hydrogen peroxide source and an organic acid wherein said composition compris s a pH of from 7.5 to 12.7.

60. (Once Amended) A method of cleaning teeth and/or mouth comprising the administration of a cleaning composition comprising a surfactant system, an oxidoreductase with an α/β-hydrolase fold and a catalytic triad consisting of the amino acid residues serine, histidine and aspartic acid, a hydrogen peroxide source and an organic acid wherein said composition comprises a pH of from 7.5 to 12.7.

SEP-23-2002 10:48

- 61. (Once Amended) A method of sanitisation comprising the step of contacting a fabric, a hard surface or a dishware with a cleaning composition comprising a surfactant system, an oxidoreductase with an α/β-hydrolase fold and a catalytic triad consisting of the amino acid residues serine, histidine and aspartic acid, a hydrogen peroxide source and an organic acid wherein said composition comprises a pH of from 7.5 to 12.7.
- 62. (Once Amended) A method of sanitisation of teeth and/or mouth comprising the administration of a cleaning composition comprising a surfactant system, an oxidoreductase with an α/β-hydrolase fold and a catalytic triad consisting of the amino acid residues serine, histidine and aspartic acid, a hydrogen peroxide source and an organic acid wherein said composition comprises a pH of from 7.5 to 12.7.